



## Xport™ 单点注油器



**Xport Classic 注油器**

润滑剂注量

120 cc (4.06 fl oz)

外壳设计  
金属

注油周期

1、3、6 或 12 个月 (激发剂)

运行温度范围

0 到 40°C (32 到 104°F)

最大工作压力

4 bar / 58 psi

**Xport Futura 注油器**

润滑剂注量

120 cc (4.06 fl oz)

外壳设计  
透明塑料

注油周期

1、3、6 或 12 个月 (激发剂)

运行温度范围

0 到 40°C (32 到 104°F)

最大工作压力

4 bar / 58 psi

**Xport™ Flex 注油器**

润滑剂注量

60 或 125 cc (2.03 或 4.23 fl oz)

外壳设计  
透明塑料

注油周期

1、2、3.....12个月 (转盘)

运行温度范围

-20 到 60°C (-4 到 140°F)

最大工作压力

5 bar / 72.5 psi

**Xport™ Nova 注油器**

润滑剂注量

125 cc (4.23 fl oz)

外壳设计  
透明塑料

注油周期

1、2、3.....12个月 (按钮)

运行温度范围

-20 到 60°C (-4 到 140°F)

最大工作压力

6 bar / 87 psi



**Xport Star Vario / Star Control 注油器**

润滑剂注量

60、125 或 250 cc (2.03、4.23 或 8.45 oz)

注油周期

Star Vario - 1、2、3.....12个月 (按钮)

Star Control - 时间或脉冲控制

运行温度范围

-10 到 60°C (14 到 140°F)

最大工作压力

max. 6 bar / 87 psi



## Xport™ 单点注油器

### 适用性

		输送机	电动机	泵	吹风机/鼓风机
	<b>Classic &amp; Futura</b>	++	○	+	+
	<b>Flex</b>	+	+	++	++
	<b>Nova</b>	+	++	+	++
	<b>Star Vario &amp; Star Control</b>	++	++	++	++

○ 适用性有限

+ 适用

++ 理想之选



LEX-SPLLCFLY\_132 5-16, rev. 10-17