

Product Information



Xport® Lubricant Application

Xport® Grease Spray System

Lubricant protection delivered quickly and easily while maintaining safe distance from hazardous areas.

The Xport® Grease Spray System is a pneumatic pump system that fits onto LE's pail or quarter drum and is recommended for greasing the tires and wear bars of kilns. It allows quick and easy lubrication, despite the high temperatures and rotating equipment associated with kilns.

The spray system helps reduce time of application with its 2-lb (0.9-kg)-plus-per-minute application rate, and it eliminates the time spent replacing or disposing of tube cartridges. The system requires plant air of 90-100 psi (6.2-6.9 bar). It comes with a 36- or 59-inch (91- or 150-cm) long chrome-insulated applicator lance to allow personnel to maintain a safe distance from potentially hazardous areas.

Benefits

- Two length options
- Easy to use
- No leaks, no mess
- Durable and dependable
- Superior quality



Item #	Fits LE Container	Lance Length	Max Pressure	Max Flow	Max Temperature	Connectors	System Contents
LEX-SPRLAN35PL-COKT	Pail	36- or 59-inch (91 or 150 cm)	5,000 psi (345 bar)	12 gpm (45 lpm)	300°F (149°C)	¼-inch (0.6 cm) MNPT on both sides	Spray handle, lance, ¼" (0.6 cm) high impact spray head, 7' x ¼" ID (2 m x 0.6 cm) braided wire hose, pump, follower plate, pump cover)
LEX-SPRLAN120KG-COKT	Quarter Drum						

Xport® is a registered trademark of Lubrication Engineers, Inc.

LEX-LPASLS_FLY_198 5-24



1919 E. Tulsa • Wichita, KS 67218 • Fax: 800-228-1142
LE operates under an ISO 9001 Certified Quality System.

www.LElubricants.com • 800-537-7683